


W 632 SERIES



ADO

**PVC PROFILE
TECHNICAL SPECIFICATION**





TECHNICAL

W 630 - W 632 SERIES

Profile Width: 60 mm

Number of chambers: 3

Profile Class: W 632 B Class (TS EN 12608-1), W 630 C Class (TS EN 12608-1)

Seal Type: External / Internal double seal system

Seal Type and Color: TPE - Grey /Black
















Glass Thickness (mm): 4, 20, 24, 30, 32 mm


The thermal insulation Uf: 1,58 W/m²K

INSTRUCTION


- The main profile has 60 mm width.
- Because of the elastic grey and black seal which does not leave any stain on profiles will be provided maximum air, water, dust and sound isolation.
- Due to the 3 chambers profiles, it has maximum performance for thermal, sound and water isolation.
- It is a series of profiles with very special design that provides maximum wind resistance on high rise buildings.
- Excluding normal sash profile there is also chance to have a choice for offset type sash profile.
- In addition to white profile a different laminated color range is available.
- 4-5 mm single glazing application of 20, 24, 30, 32 mm glazing beads give us alternatives of using double, triple glazing and panels.
- It provides the visual integrity in the inner surface and the frame-wall connections due to integrated frame with sill profile.

W 630 - W 632 SERIES PVC PROFILE SYSTEM







Outward Opening Eco Door Sash Profile
632.2108




Outward Opening Door Sash Profile
632.2101




Lap Joint Profile
632.3104




Lap Joint Profile
632.3100




Single Glazing Bead 4-6 mm
101.4002




Double Glazing Bead 20 mm
101.4100




Double Glazing Bead 20 mm
101.4102




Double Glazing Bead 24 mm
750.4500




Double Glazing Bead 24 mm
101.4202




Double Glazing Bead 30 mm
332.4100




Double Glazing Bead 32 mm
101.4500




Offset Profile
900.6307



Frame Sill Profile (35mm)
099.5523




Frame Sill Profile (50mm)
099.5524




Universal Short Coupling Profile
099.5004




Universal Large Coupling Profile Cover
058.5707




Narrow Couple Profile
060.5001




Short Coupling Profile
099.5003




Sill Profile
058.5504




Universal Large Coupling Profile
058.5000




Large Coupling Profile
060.5000



60x100 Spiked Box Profile
060.5203 0







60x100 Frame Lifting Profile
900.5303

















135° Corner Profile
060.5102


W 630 - W 632 SERIES PVC PROFILE SYSTEM




W 632 Re-Inforcement Profiles




W 632 Installation




Frame - Sash Installation




Frame - Offset Type Sash Installation




Frame with Sill - Sash Installation




Frame with Sill (60mm) - Sash Installation




Mullion - Sash Installation




Frame - Outward Opening Sash Installation




Frame - Door Sash Installation




Sash - Lap Joint - Sash Installation



Frame - Outward Opening Door Sash Installation




With Aluminium Threshold Frame Door Sash Installation



Narrow Coupling Profile Installation

W 630 - W 632 SERIES PVC PROFILE SYSTEM





www.ado.com.tr

FACTORY

Antalya Organize Sanayi Bölgesi 2.Kısım Mah. 21.Cadde No:3

07040 Döşemealtı / ANTALYA / TURKEY

Tel : +90 242 236 20 00 · Faks : +90 242 236 20 90 · Email : info@ado.com.tr



JULY / 2021